

TECHNICAL DATA SHEET

# EFCO ATEX Rewind cable reel KPE

### 1. Product description

Rewind cable reel for equipotential bonding and for dissipating electrostatic charges, conformity according to 2014/34/EU (ATEX).

# 2. Applications

The rewind cable reel KPE corresponds to ATEX equipment class II in categories 3G and 3D. It is therefore intended for use in EX zones 2 and 22.

# 3. Properties

• Especially for electrostatic equipotential bonding compliant with ATEX

 Protected against dust and splashing water in accordance with IP protection class IP 64

- · Compact design
- · Automatic cable retraction
- · Cable lock can be switched on and off
- · Casing made of high quality glass-fibre reinforced plastic
- · High-quality INOX cable with PUR sheath
- · Guide rollers for gentle cable guidance
- Dust-protected, closed rotary coupling with triple contact transmission
- · Can be installed in 6 different positions
- · Swiss made

### 4. Technical data

Protection class

Gas: II 3G Ex eb IIC T6 Gb

Dust: II 3D Ex tb IIIC T80 °C Db

IP protection class IP 64

Ambient temperature  $(T_{am b})$   $-20 \,^{\circ}\text{C} \leq T_{amb} \leq +60 \,^{\circ}\text{C}$ 

Enclosure material Glass-fibre reinforced polyamide

Compensating conductor Stainless steel, 2 mm dia., sheathed in PUR, 7.75 mm dia.


Connecting cable  $\geq 3 \, \text{mm}^2$ 

Cable length 8 m (other lengths on request) Dimensions (L×W×H)  $300 \times 230 \times 155 \text{ mm}$  (w/o clamp)


Weight 3.1kg including clamp

Colour Yellow










90°





# 4. Technical Data (cont.)



# 5. Inspections/approvals/performance specifications/conformity

- EU type examination certificate compliant with 2014/34/EU
- · Conformity to standards
  - EN ISO/IEC 60079-0: 2018
  - EN ISO/IEC 60079-7: 2015
  - EN ISO/IEC 60079-31: 2014
  - Internal production control according to RL 2014/34/EU Annex VIII
  - EFCO is EX-certified company according to EN ISO/IEC 80079-34:2017
- · Environmentally compliant in accordance with
  - Regulation EC No. 1907/2006 (REACH) (dated 20/02/2020)
  - Directive 2015/863/EU (RoHS) (dated 20/02/2020)

All certificates are available for download on the EFCO website: www.efco.swiss



# 5. Inspections/approvals/performance specifications/conformity (cont.)

smart fixing

### **EU Conformity Declaration**

- 1. Product model/product EX rewind cable reel, type: KPE
- 2. Name and address of manufacturer EFCO Fixing Technology Ltd, Grabenstrasse 1, 8606 Nänikon, Switzerland
- 3. The manufacturer bears the sole responsibility for issuing the conformity declaration.
- 4. Subject of the declaration EX rewind cable reel, type: KPE
- 5. The subject of the declaration described above complies with the European Union's relevant harmonisation legislation:

#### DIRECTIVE 2014/34/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL dated 26 February 2014

6. Indication of the relevant harmonised standards or of the other technical specifications on which the declaration of conformity was based:

EN ISO/IEC 60079-0: 2018 EN ISO/IEC 60079-7: 2015 EN ISO/IEC 60079-31: 2014

7. Additional information: none Internal production control according to RL 2014/34/EU Annex VIII EFCO is EX-certified company according to EN ISO/IEC 80079-34:2017

Signed for and in the name of:

EFCO Fixing Technology Ltd Grabenstrasse 1, 8606 Nänikon, Switzerland

Nänikon, 21/02/2020

Thomas Doppelbauer, Quality Manager

EFCO Fixing Technology Ltd Phone +41 209 81 11 Grabenstrasse 1 8606 Nänikon, Switzerland Web www.efco.swiss

Email info@efco.swiss

Page 1/1



# 5. Inspections/approvals/performance specifications/conformity (cont.)





### 6. Operating Instructions

The operating instructions are available for download on the EFCO website: www.efco.swiss

### 7. Disposal

The cable reel consists of plastic (PA), steel and non-ferrous metal in minor quantities. The respective national or regional waste disposal regulations apply.

# 8. Manufacturer/brand/production

EFCO Fixing Technology Ltd
Grabenstrasse 1 · 8606 Nänikon · Switzerland

### 9. Article data

EFCO Art. No	Designation	Including bracket	Clamp	PU
D83.206	KPE EX-II 3G 3D	110.5×89×64.5 mm, galvanised	Not insulated	1
D83.207	KPE EX-II 3G 3D	110.5×89×64.5 mm, galvanised	Insulated	1
D83.220	KPE EX-II 3G 3D with supply cable	110.5×165×75 mm, Inox A2	Not insulated	1

#### **ACCESSORIES**

#### Clamps

EFCO Art. No	Designation	Version	Span (mm)	PU
D83.213	Clamping tongs ZI	Insulated	30	1
D83.214	Clamping tongs ZNI INOX	Not insulated	45	1



#### Equipotential bonding cable

- Inox A2 1x3 mm², steel cable, yellow/green
- · Inox A2 clamping tongs material

EFCO Art. No	Designation	Effective length (m)	PU
D84.000	Equipotential bonding cable 2.5 m clamps at both ends	2.5	1
D84.001	Equipotential bonding cable 4 m clamps at both ends	4	1
D84.005	Equipotential bonding cable 5 m clamps at both ends	5	1



Additional accessories available on request.

#### 10. Links/downloads

You can find additional information at:

EFCO-Website/EFCO-Online-Shop http://www.efco.swiss CLIC-Website http://www.clic.swiss



The information given is based on our current technical knowledge and is intended as a guide. In specific cases, it might be necessary to clarify the chemical resistance using your own tests.

Contact EFCO for further technical information.